## IMPROVE DOCK & DOOR AND WORKSTATION ENVIRONMENTS Increase employee safety and productivity around your team's

Ioading docks
Add directional lighting and air movement inside trailers, around the harsh loading dock areas, or at machine stations.

## WALL-MOUNTED ARTICULATING ARM

- Wide range of articulation to direct airflow and light where it is needed most
- Compatible with 12", 20", or 24" Jan Fan Industrial Air Circulators
- Rugged twin-strut steel arm with reach up to 45 inches
- Fan and Light can be mounted simultaneously
- Safety Yellow for enhanced visibility
- Meets OSHA requirements

## **HIGH POWER LED LIGHT**

- Durable aluminum housing and rugged components designed to withstand industrial applications
- Compatible with 12", 20", or 24" Jan Fan Industrial Air Circulators
- Fan and Light can be mounted simultaneously
- "Safety Yellow" for enhanced visibility
- Cool to the touch
- 50,000-hour LED life
- ETL/cETL/CE/RoHS/UL

## FAN & LIGHT ARTICULATING ARM









| LED Dock Light        |                       |  |  |  |  |  |  |
|-----------------------|-----------------------|--|--|--|--|--|--|
| Part Number           | JF-DL                 |  |  |  |  |  |  |
| Watt                  | 30W                   |  |  |  |  |  |  |
| Total Lumens          | 3300 LM               |  |  |  |  |  |  |
| Dimensions (LxWxH)    | 4.21" X 5.51" X 5.51" |  |  |  |  |  |  |
| Power Cord Length     | 8'                    |  |  |  |  |  |  |
| Beam Angle            | 36 DEGREES            |  |  |  |  |  |  |
| Surge Voltage         | 6KV                   |  |  |  |  |  |  |
| CCT                   | 3000K-6000K           |  |  |  |  |  |  |
| Input Voltage         | AC 100-277V, 50-60Hz  |  |  |  |  |  |  |
| CRI                   | >80                   |  |  |  |  |  |  |
| Power Factor          | >0.9                  |  |  |  |  |  |  |
| Operating Temperature | -40C to 60C           |  |  |  |  |  |  |
| IP Rating             | IP65                  |  |  |  |  |  |  |
| Test Standard         | IES/LM79/LM80         |  |  |  |  |  |  |
| Safety Certification  | ETL/CETL/CE/ROHS/UL   |  |  |  |  |  |  |
| Housing               | ALUMINUM              |  |  |  |  |  |  |
| Cage                  | STAINLESS STEEL       |  |  |  |  |  |  |
| LED Life              | 50,000 HOURS          |  |  |  |  |  |  |
| Warranty              | 5 Years               |  |  |  |  |  |  |

| Articulating Arm Mount |                       |  |  |  |  |  |  |
|------------------------|-----------------------|--|--|--|--|--|--|
| Part Number            | JF-AAM                |  |  |  |  |  |  |
| Construction           | Steel                 |  |  |  |  |  |  |
| Extended Length        | 45 Inches             |  |  |  |  |  |  |
| Dimensions (LxWxH)     | 45" x 1.97" x 5.91"   |  |  |  |  |  |  |
| Max. Weight Capacity   | 55 lbs                |  |  |  |  |  |  |
| Articulation           | 350 Degrees           |  |  |  |  |  |  |
| Mount Type             | Wall                  |  |  |  |  |  |  |
| Color                  | Safety Yellow         |  |  |  |  |  |  |
| Fan Compatible         | Jan Fan 12", 20", 24" |  |  |  |  |  |  |
| Light Compatible       | JF-DL                 |  |  |  |  |  |  |
| Safety Requirements    | OSHA                  |  |  |  |  |  |  |
| Warranty               | 5 Years               |  |  |  |  |  |  |

| Part Number  | Fan Product Description  | Length | Width  | Height | Power<br>Cord<br>Length | Weight<br>(LB) | CFM   | dBa | RPM (H/L) | Blade<br>Diameter | Guard<br>Balde<br>Dia. |
|--------------|--|--------|--------|--------|-------------------------|----------------|-------|-----|-----------|-------------------|------------------------|
| JF-AKF20-DCS | 20" - 2 SPEED ADAPTOR KIT MOUNT FAN COMPLETE W/<br>DROP CORD                               | 13.75" | 24.6"  | 24.6"  | 18'                     | 39             | 4,250 | 60  | 1100/900  | 20"               | 24.6"                  |
| JF-AKF24-DCS | 24" - 2 SPEED ADAPTOR KIT MOUNT FAN COMPLETE W/<br>DROP CORD                               | 13.75" | 30.6"  | 30.6"  | 18'                     | 46             | 6,210 | 64  | 1100/900  | 24"               | 30.6"                  |
| JF-12F       | 12" 3 SPEED INDUSTRIAL WORKSTATION FAN COMPLETE<br>W/STAND AND YOKE MOUNT. FULLY ASSEMBLED | 6.5"   | 16.25" | 15"    | 10'                     | 12             | 2,375 | 44  | -         | 12"               | 14"                    |